

PACi Elite and Standard 4 Way 60x60 Cassette Inverter+ • R32 GAS

Small and powerful, ideal for offices and restaurants

Standard units only for Twin, Triple and Double-twin combinations.



CZ-KPY3AW
Panel 700 x 700mm.

CZ-KPY3BW
Panel 625 x 625mm.



CZ-RWS3
Optional Controller.
Infrared remote controller.



CZ-RE2C2
Optional Controller.
Simplified remote controller.

			Single Phase	
			3,60kW	5,00kW
KIT			KIT-36PY2ZH5	KIT-50PY2ZH5
Remote controller			CZ-RTCS5B	CZ-RTCS5B
Cooling capacity	Nominal (Min - Max)	kW	3,60(1,50 - 4,00)	5,00(1,50 - 5,60)
EER ¹⁾		W/W	4,68	3,68
SEER ²⁾			6,60 A++	6,40 A++
Pdesign		kW	3,60	5,00
Input power cooling		kW	0,77	1,36
Annual energy consumption ³⁾		kWh/a	191	273
Heating capacity	Nominal (Min - Max)	kW	4,00(1,50 - 5,00)	5,60(1,50 - 6,50)
COP ¹⁾		W/W	4,26	3,46
SCOP ²⁾			4,60 A++	4,30 A+
Pdesign at -10°C		kW	3,60	4,50
Input power heating		kW	0,94	1,62
Annual energy consumption ³⁾		kWh/a	1096	1465
Indoor unit			S-36PY2E5B	S-50PY2E5B
Air volume	Hi / Med / Lo	m ³ /min	9,7/8,0/6,0	11,1/9,8/8,5
Moisture removal volume		L/h	1,5	2,4
Sound pressure ⁴⁾	Hi / Med / Lo	dB(A)	36/32/26	40/37/33
Sound power	Hi / Med / Lo	dB	51/47/41	55/52/48
Dimension (HxWxD) / Net weight	Indoor	mm / kg	288x583x583/18	288x583x583/18
	CZ-KPY3AW Panel	mm / kg	31x700x700/2,4	31x700x700/2,4
	CZ-KPY3BW Panel	mm / kg	31x625x625/2,4	31x625x625/2,4
Outdoor unit			U-36PZH2E5	U-50PZH2E5
Power source		V	220/230/240	220/230/240
Current	Cool (Hi / Med / Lo)	A	3,65/3,50/3,35	6,35/6,10/5,85
	Heat (Hi / Med / Lo)	A	4,50/4,30/4,15	7,70/8,40/8,10
Air volume	Cool / Heat	m ³ /min	40/40	40/45
Sound pressure	Cool / Heat (Hi)	dB(A)	43/44	45/48
Sound power	Cool / Heat (Hi)	dB	62/64	64/68
Dimension / Net weight	HxWxD	mm / kg	695x875x320/43	695x875x320/43
Piping connections	Liquid pipe	Inch (mm)	1/4(6,35)	1/4(6,35)
	Gas pipe	Inch (mm)	1/2(12,70)	1/2(12,70)
Pipe length range		m	3 - 40	3 - 40
Elevation difference (in/out) ⁵⁾		m	30	30
Pipe length for additional gas		m	30	30
Additional gas amount		g/m	20	20
Refrigerant (R32) / CO ₂ Eq.		kg / T	1,15/0,776	1,15/0,776
Operating range	Cool Min ~ Max	°C	-15 ~ +46	-15 ~ +46
	Heat Min ~ Max	°C	-20 ~ +24	-20 ~ +24



SEER and SCOP: For KIT-36PY2ZH5. INTERNET CONTROL: Optional.

Compatible with all Panasonic connectivity solutions. For detailed information go to the Control Systems section.