

Insulated collar thickness $\varnothing 13$ and $\varnothing 19$

SCC600063 - SCC600064 - SCC600065
 SCC600066 - SCC600067 - SCC600068
 SCC600069 - SCC600070 - SCC600071
 SCC600072 - SCC600073 - SCC600074
 SCC600075 - SCC600076



TECHNICAL SPECIFICATIONS:

- Galvanised steel
- Includes joining screws and plug
- Polyurethane foam (PIR) coupled with flexible elastomer foam (FEF) and PVC outer coating
- External black colour
- Thickness 13 mm or 19 mm
- Operating temperature MAX: + 120°C / MIN. - 180°C.
- Reaction to fire class: B2

TECHNICAL DATA

CODE	SCREW	DOWEL [mm]	COLLAR DIMENSIONS [INCH]	PACK: MIN. OF
SCC600063	M8 x 90	$\varnothing 10 \times 60$	1" 1/4	10 pc.
SCC600064	M8 x 90	$\varnothing 10 \times 60$	1" 1/4	10 pc.
SCC600065	M8 x 90	$\varnothing 10 \times 60$	1" 1/4	10 pc.
SCC600066	M8 x 90	$\varnothing 10 \times 60$	1" 1/2	10 pc.
SCC600067	M8 x 90	$\varnothing 10 \times 60$	1" 1/2	10 pc.
SCC600068	M8 x 90	$\varnothing 10 \times 60$	2"	10 pc.
SCC600069	M8 x 90	$\varnothing 10 \times 60$	2"	10 pc.
SCC600070	M8 x 90	$\varnothing 10 \times 60$	1" 1/2	10 pc.
SCC600071	M8 x 90	$\varnothing 10 \times 60$	1" 1/2	10 pc.
SCC600072	M8 x 90	$\varnothing 10 \times 60$	1" 1/2	10 pc.
SCC600073	M8 x 90	$\varnothing 10 \times 60$	2"	10 pc.
SCC600074	M8 x 90	$\varnothing 10 \times 60$	2"	10 pc.
SCC600075	M8 x 90	$\varnothing 10 \times 60$	2" 1/2	10 pc.
SCC600076	M8 x 90	$\varnothing 10 \times 60$	2" 1/2	10 pc.

ITEMS

CODE	DESCRIPTION
SCC600063	
SCC600064	
SCC600065	
SCC600066	
SCC600067	
SCC600068	
SCC600069	
SCC600070	
SCC600071	
SCC600072	
SCC600073	
SCC600074	
SCC600075	
SCC600076	