

## Sauermann® part #: PE5100SIUN23

# PE 5100

## PERISTALTIC PUMP





## **Compact pump**

The peristaltic pump is controlled by 2 thermal probes. When the temperature difference reaches 6  $^{\circ}$  C, the pump runs. It stops 3 minutes after the temperature difference is fallen below 6  $^{\circ}$  C.

This pump must not be used in continuously run.

## **BENEFITS**



#### High performance

- High discharge head up to 12m.
- Low noise level

## Easy to install

- Compact design.
- IP65 protection allows installation without ventilation.





## Easy and quick maintenance

Its replaceable head and easy access tube reduce maintenance costs

## **KIT CONTENT**

- Peristaltic pump PE 5100
- Cable: 1.7 m, including 2 wires for power supply (P &N).
- 2 thermal probes with 3.5m cable:
  - Red cap for ambient air.
  - Blue cap for fresh air.
- Easy "1 screw" sliding plastic bracket
- Ø 15 mm to Ø 6 mm adaptor + pale yellow rubber (Ø 15 x 35mm) (PE5003)

## **APPLICATIONS**

## For use with any air-conditioning units up to 8 kw

- Wall mounted
- Computer room air conditioning
- Ceiling suspended
- Ducted





TECHNICAL SPECIFICATION		
Max. flow rate	6 l/h	
Max suction head	2 m	
Max discharge head	12 m	
Sound level in application at 1m: (Measured in Sauermann acoustic lab, pump operating with water)	≤ 30 dBA	
Mains supply	230V~ 50Hz - 11 W	
Insulation class	(double insulation)	
Detection type	2 thermal probes	
Protection	IP65	
Pump dimensions (LxWxH)	109 x 110 x 91 mm	
Safety standards	CE & EAC	
RoHS directive	Compliant	
WEEE directive	Compliant	
Packaging	1.15 kg	
Masterpack	16 pieces	

ACTUAL FLOW RATE (I/h)		
		Tube (Ø Int 6 mm, 1/4")
Max suction	Max discharge	The discharge flow is constant whatever the
head	head	discharge or the suction head
2 m	12 m	6



**RECOMMANDED ACCESSORIES** 



## Clear PVC hose Ø int. 6mm (1/4")

ACC00105:5 m ACC 00150: 50 m

ACC 00151: Braided, 50 m



Float detector, used to operate an additional alarm or to switch on the pump ACC 00601



Adaptor + pale yellow rubber To reduce diameter from Ø int. 15mm (3/5") to Ø int. 6mm

(1/4")PE 5003



Replacement head for PE5000, PE5100 and PE5200

PE 5001



6 Self-sealing fittings for hose

Ø int. 6 mm (1/4") ACC 00205



Replacement tube for PE5000, PE5100 and PE5200

PE 5002