EC 56 EASY FIT



Self Contained Ice Machine up to 35 kg

ltem #:	
Project:	
Quantity:	



FEATURES

- Produces individual Gourmet crystal clear supercubes.
- Resistant stainless steel exterior. Simple and reliable electrome-
- Front panel in and out airflow (air cooled model only) for built-in installation.
- Front access condenser air filter, removable and washable (air cooled model only).
- Easily accessible front ON-OFF switch. Routine maintenance visible alarm light on front panel.
- Ergonomically designed ice storage access, with disappearing door. Door-closing movement dampening system.
- Water system protected by patented anti-scale system.
- PWD Progressive Water Discharge: pumps excess residual water up to a distance of 15 meters.



EC L 56 Large Gourmet 39 g Ø 38 x H 41 mm



EC M 56 Medium Gourmet 20 g Ø 30 x H 34 mm



EC S 56 Small Gourmet 8 g Ø 21 x H 25 mm

CONDENSING SYSTEM	INTERNAL BIN CAPACITY				
Air cooled Water cooled		12 kg			
REFRIGERANT GAS	OPERATING REQUIREMENTS				
R134a		Minimum	Maximum		
	Air temperature	10°C	43°C		
VOLTAGE V/Hz/ph	Water temperature	5°C	38°C		
230(60/1 230/50/1	Water pressure	1 bar (14 psi)	5 bar (70 psi)		
230/60/1	Electrical voltage	-10%	+10%		

Certifications:























EC 56 EASY FIT





Self Contained Ice Machine up to 35 kg

Item #:
Project:
Quantity:










UNIT OF MEASUREMENT: mm

- 1. 3/4" OD OVERFLOW DRAIN
- 2. 3/4" GAS WATER INLET
- 3. 3/4" GAS WATER OUTLET WATER COOLED UNIT ONLY
- **4.** 3/4" GAS WATER INLET WATER COOLED UNIT ONLY
- 5. CORD SET



UNIT DATA

Size (W x D x H)

386 x 600 x 695 mm

Net weight 38 kg

SHIPPING DATA

Carton (W x D x H) 460 x 670 x 810 mm

Weight 45 kg

		Compressor		Circuit	Max. fuse size	
Version	Voltage	Btu/h	w	No.	Ømm²	Α
EC L 56 AS	230/50/1	2730	800	3	1.5	10
EC L 56 AS	230(60/1	3071	900	3	1.5	10
EC M 56 AS	230/50/1	2730	800	3	1.5	10
EC M 56 AS	230/60/1	3071	900	3	1.5	10
EC S 56 AS	230/50/1	2730	800	3	1.5	10
EC L 56 WS	230/50/1	2730	800	3	1.5	10
EC M 56 WS	230/50/1	2730	800	3	1.5	10

			24 h ice production kg °C Amb. / °C Water		Energy consumption*		Water usage*	Instant power	
Version	Condensation	Voltage	10°C/10°C	21°C/10°C	32°C/21°C	kWh/100 kg	kWh/24h	l/h	W
EC L 56 AS	Air	230/50/1	31	30	23	33.1	7.6	4.2	400
EC L 56 AS	Air	230(60/1	35	34	27	32.3	8.6		470
EC M 56 AS	Air	230/50/1	32	31	24	33.0	7.9	3.8	400
EC M 56 AS	Air	230/60/1	35	34	27	32.3	8.6	20.2	470
EC S 56 AS	Air	230/50/1	25	24	19	38.6	7.1	3.1	400
EC L 56 WS	Water	230/50/1	31	30	23	33.1	7.6		400
EC M 56 WS	Water	230/50/1	33	31	27	26.0	7.0	20.2	400

^(*) Data refer to 32°C Amb. / 21°C Water temperature conditions