AFC 134

Scotsman[®]

Self Contained Ice Machine up to 130 kg

ltem #:	
Project:	
Quantity:	



FEATURES

- Produces "Cubelet" ice (compressed ice flakes). Ice scoop holder located within ice-storage bin.
- Resistant stainless steel exterior.
- Reliable electronic controls.
- Front panel in & out airflow (air-cooled model only) for built-in installation.
- Front access condenser air filter, removable and washable (air cooled version only). Optional "Demineralized Water" adaptor
- Easily accessible front panel mount ON-OFF Switch.
- Routine Maintenance visible alarm light on front panel.
- Ergonomically designed ice-storage access, with disappearing door. Door-closing movement dampening system.



AFC 134 Cubelet 1 a W 16 x D 15 x H 7-8 mm

CONDENSING SYSTEM	INTERNAL BIN CAPACITY				
Air cooled Water cooled	40 kg				
REFRIGERANT GAS	OPERATING REQUIREMENTS				
R404A		Minimum	Maximum		
	Air temperature	10°C	43°C		
VOLTAGE V/Hz/ph	Water temperature	5°C	38°C		
230/50/1	Water pressure	1 bar (14 psi)	5 bar (70 psi)		
230/60/1	Electrical voltage	-10%	+10%		

Certifications:



















AFC 134





Self Contained Ice Machine up to 130 kg

Item #:
Project:
Quantity:










UNIT OF MEASUREMENT: mm

- 1. 25/32" OD OVERFLOW DRAIN
- 2. 3/4" GAS WATER INLET
- 3. 3/4" GAS WATER OUTLET WATER COOLED UNIT ONLY
- 4. 3/4" GAS WATER INLET WATER COOLED UNIT ONLY
- 5. CORD SET



UNIT DATA

Size (W x D x H) 950 x 605 x 872 mm

Net weight 68 kg

		Compressor		Circuit	Max. tuse size		
Version	rsion Voltage		W	No.	Ømm²	Α	
AFC 134 AS	230/50/1	4606	1350	3	1.5	10	
AFC 134 WS	230/50/1	4606	1350	3	1.5	10	
AFC 134 AS	230/60/1	4606	1350	3	1.5	10	

SHIPPING DATA

Carton (W x D x H) 1030 x 680 x 960 mm

Weight 79 kg

			24 h ice production kg °C Amb. / °C Water			Ene consum	37	Water usage*	Instant power
Version	Condensation	Voltage	10°C/10°C	21°C/10°C	32°C/21°C	kWh/100 kg	kWh/24h	l/h	W
AFC 134 AS	Air	230/50/1	130	127	92	14.9	13.7	3.8	600
AFC 134 WS	Water	230/50/1	130	124	110	11.0	12.2	59.4	500
AFC 134 AS	Air	230/60/1	130	127	92	14.9	13.7	3.8	600

(*) Data refer to 32°C Amb. / 21°C Water temperature conditions